

抽真空軟板快速壓機

VACUUM HIGH SPEED  
FLEXIBLE BOARD  
LAMINATING MACHINE

VIGOR



VFPC1-15  
VFPC1-15V  
VFPC2-15V

活全機器股份有限公司  
VIGOR MACHINERY CO., LTD.

[www.supvigor.com.tw](http://www.supvigor.com.tw)



## ■ 特性

1. 單片壓合，機器設計體積縮小，室內任何位置擺置皆方便，不佔空間。
2. 配合快速膠，快速生產，打樣與量產皆合適。
3. 單面板預壓約 5 秒，上壓約 15~60 秒，雙面板預壓約 5 秒，上壓約 90~120 秒。
4. 操作簡便，無複雜教育訓練，上線容易。
5. 採真空壓合，可達 10Torr 以上真空度。
6. 可降低壓合壓力，減少壓合成品翹曲。
7. 有效增加副資材使用壽命。
8. 有效減少轉印效果。

## ■ 用途

軟式印刷線路板與覆蓋膜之壓合。

## ■ FEATURES

1. Designed for single sheet pressing operations. The machine is compact constructed for working at any location in a room for space saving.
2. Accommodates instant glue for high production rate. Ideal for both sampling and mass production requirements.
3. Pre-pressing for single surface board is about 5 seconds, and about 15~60 seconds for top pressing. Pre-pressing for double surface board is about 5 seconds, and about 90~120 seconds for top pressing.
4. Easy to operate without special operation training is required.
5. The machine is based on vacuum pressing system, its vacuum status will be over than 10 Torr.
6. It capable of reducing the pressure for pressing process. To eliminate the finished product with curved problem after pressing process.
7. To add the operation life of auxiliary material effectively.
8. To reduce the imprint problem effectively.

## ■ APPLICATION

Suitable for pressing cover ray on the flexible printing circuit board.

## 規格表 SPECIFICATIONS

項目 ITEM	型號 MODEL	VFPC1-15	VFPC1-15V	VFPC2-15V
總出力	Tonnage	150 Tons	150 Tons	150 Tons
油缸直徑	Ram diameter	φ 355 mm	φ 355 mm	φ 355 mm
床台面積	Table dimension	600 x 600 mm	600 x 600 mm	600 x 660 mm
有效壓合尺寸	Effective pressing area	550 x 580 mm	550 x 580 mm	545 x 630 mm
面壓	Pressure on platen	Max 50 kg/cm <sup>2</sup> (可調整 adjustable)	Max 50 kg/cm <sup>2</sup> (可調整 adjustable)	Max 50 kg/cm <sup>2</sup> (可調整 adjustable)
工作壓力	Working pressure	Normal: 152 kg/cm <sup>2</sup> , Max 162 kg/cm <sup>2</sup>	Normal: 152 kg/cm <sup>2</sup> , Max 165 kg/cm <sup>2</sup>	Normal: 152 kg/cm <sup>2</sup> , Max 165 kg/cm <sup>2</sup>
所需電源	Electricity	3 φ 220V / 380V / 440V, 50 / 60HZ		
所需電量	Power consumption	21.5 kw	22 kw	22 kw
真空度	Vacuum degree	20torr / 3sec		
機械尺寸(長x寬x高)	Machine dimensions (LxWxH)	1550 x 1200 x 1800 mm	1550 x 1200 x 1800 mm	1550 x 1200 x 1800 mm
機器圖稿	Machine drawing	VFPC1-15A(附光幕With light curtain)	VFPC1-15V5(附光幕With light curtain)	VF-35V00B
使用溫度	Temperature	MAX: 220°C		
溫度精度	Temperature accuracy	180°C ± 3.5°C (以料溫線九點測量 Use temperature wire to measure at 9 points)	180°C ± 3.5°C (以料溫線九點測量 Use temperature wire to measure at 9 points)	180°C ± 3.5°C (以料溫線九點測量 Use temperature wire to measure at 9 points)
機器重量	Machine weight	3400 kgs	3450 kgs	3500 kgs

※本資料解釋權歸活全機器股份有限公司所有。 ※ Copy right by VIGOR MACHINERY CO., LTD.

## 活全機器股份有限公司 VIGOR MACHINERY CO., LTD.

台中縣霧峰鄉五福路 7 9 8 號  
NO. 798, Wu-Fu Rd., Wu-Feng Hsiang, Taichung Hsien, Taiwan.  
Tel: 886-4-2331-3388 Fax: 886-4-2331-3377 <http://www.supvigor.com.tw>  
E-mail: c.s.huang@seed.net.tw E-mail: sa-2@supvigor.com.tw

大陸辦事處:  
廣東省東莞市長安鎮新安社區新安二路9號城市花園B3-12D  
Tel: 0769-2399-4598 Fax: 0769-8238-1276 服務專線: 13609685297

江蘇省蘇州市吳中區碧波街遠洋花園4單元307室  
Tel: 0512-6267-5616 Fax: 0512-6513-8125 服務專線: 13776097137